

DOCKET NO. SC11493TH

Please enter the following amendments:

In the Claims:

1. (Original) A method of program execution in a data processing system comprising:

means for fetching a first instruction located at a first address; and

means for executing the first instruction with the data processing system, the method comprising:

executing the first instruction;

selecting a jump address based upon a value by providing a second address for the jump address if a comparison of the value with a predetermined value has a first result, and providing a third address for the jump address if the comparison of the value with the predetermined value has a second result, wherein neither the second address nor the third address is contiguous to the first address; and

always implementing a change of control in the program execution in response to executing the first instruction by redirecting program execution to the jump address.

2. (Original) The method of claim 1 wherein the first result is a comparison determination that the value is greater than the predetermined value and the second result is a comparison

DOCKET NO. SC11493TH

determination that the value is less than or equal to the predetermined value.

3. (Currently Amended) The method of claim 1 further comprising:
implementing the value that is compared with the predetermined value as a count value stored in a counter.

4. (Currently Amended) The method of claim 3 wherein implementing the value that is compared with the predetermined value as a count value in a counter further comprises:

using the count value to track when a change of program tasks should be implemented by the data processing system.

5. (Original) The method of claim 1 further comprising:
generating the jump address by maintaining a program counter having an address value which gets incremented during program execution and truncating a predetermined number of low order bits of the address value and combining a resultant with an offset to create the jump address.

6. (Original) The method of claim 1 further comprising:

DOCKET NO. SC11493TH

selecting the second address and the third address to be within a predetermined range of addresses that is less than a total range of addresses within the data processing system.

7. (Original) The method of claim 1 further comprising:

selecting the second address to be within a predetermined range of addresses that is less than a total range of addresses within the data processing system.

8. (Original) The method of claim 1 further comprising:

providing a storage device having a predetermined range of addresses for storing processing instructions to be executed by the means for executing, the processing instructions arranged in groups, each group correlated to a predetermined opcode of a program.

9. (Original) The method of claim 8 wherein the opcode is a Java bytecode.

10. (Original) The method of claim 8 further comprising:

structuring the storage device in sections of a predetermined number of instruction slots, a

DOCKET NO. SC11493TH

predetermined amount of each of the sections dedicated to storage of the instructions.

11. (Original) The method of claim 8 further comprising:

directing execution of the processing instructions from one of the sections of the storage device to an address outside of the predetermined range of addresses and subsequently redirecting program execution back to a predetermined portion of another one of the sections of the storage device.

12. (Currently Amended) The method of claim 1 further comprising:

implementing the value that is compared with the predetermined value as a timed value provided by a timer, the timed value restricting execution of each program task implemented by the data processing system to a predetermined amount of time.

13. (Currently Amended) ~~A~~ The method of program execution in a data processing system ~~claim 1 further~~ comprising:

means for fetching a first instruction located at a first address; and

means for executing the first instruction with the data processing system, the method comprising:
executing the first instruction;

DOCKET NO. SC11493TH

selecting a jump address based upon a value by providing a second address for the jump address if a comparison of the value with a predetermined value has a first result, and providing a third address for the jump address if the comparison of the value with the predetermined value has a second result, wherein neither the second address nor the third address is contiguous to the first address;

always implementing a change of control in the program execution in response to executing the first instruction by redirecting program execution to the jump address; and

providing a storage device having a plurality of processing instructions to be executed by the means for executing, at least one of the plurality of processing instructions causing a hardware accelerator to perform a processing function.

14. (Currently Amended) The method of claim 13 wherein the change of control in the program execution is signaled via a handshake signal from the means for executing the first instruction to the hardware accelerator.

15. (Currently Amended) The method of claim 13 wherein the change of control in the program execution is conditional based upon either

DOCKET NO. SC11493TH

the first result of the comparison or the second result of the comparison occurring.

16. (Original) The method of claim 1 further comprising:

providing a storage device having a predetermined range of addresses for storing processing instructions arranged in groups, at least two of the groups having differing numbers of processing instructions and thus differing sizes.

17. (Currently Amended) A The method of claim 1 further of program execution in a data processing system comprising:

means for fetching a first instruction located at a first address; and

means for executing the first instruction with the data processing system, the method comprising:

executing the first instruction;

selecting a jump address based upon a value by providing a second address for the jump address if a comparison of the value with a predetermined value has a first result, and providing a third address for the jump address if the comparison of the value with the predetermined value has a second result, wherein neither the second

DOCKET NO. SC11493TH

address nor the third address is
contiguous to the first address;
always implementing a change of control in the
program execution in response to
executing the first instruction by
redirecting program execution to the
jump address; and
providing a storage device having a
predetermined range of addresses for
storing the plurality of processing
instructions arranged in groups, at least
one of the groups containing a single
instruction which causes a change of flow
to a separate memory resource in the data
processing system for permitting the
storage device to be compressed in size,
the separate memory resource containing
processing instructions correlated to a
predetermined opcode of a program.

18. (Currently Amended) A data processing system comprising:
a memory for storing a plurality of program instructions;
a processor coupled to the memory via a data bus for
fetching the plurality of program instructions from
the memory and selectively executing the plurality of
program instructions; and

DOCKET NO. SC11493TH

a storage device for storing a plurality of processing instructions to be executed by the processor, the plurality of processing instructions arranged in groups wherein each group is correlated to a predetermined one of the plurality of program instructions;

the processor executing a predetermined processing instruction at a predetermined address and selecting a jump address based upon a value by providing a first address for the jump address if a comparison of the value with a predetermined value has a first result, and by providing a second address for the jump address if the comparison of the value with the predetermined value has a second result, wherein neither the first address nor the second addresses address is contiguous to the predetermined address, execution of the predetermined processing instruction always implementing a change of control in program execution.

19. (Currently Amended) A The data processing system of claim 18 comprising:

a memory for storing a plurality of program instructions;
a processor coupled to the memory via a data bus for
fetching the plurality of program instructions from

DOCKET NO. SC11493TH

the memory and selectively executing the plurality of program instructions; and
a storage device for storing a plurality of processing instructions to be executed by the processor, the plurality of processing instructions arranged in groups wherein each group is correlated to a predetermined one of the plurality of program instructions;
the processor executing a predetermined processing instruction at a predetermined address and selecting a jump address based upon a value by providing a first address for the jump address if a comparison of the value with a predetermined value has a first result, and by providing a second address for the jump address if the comparison of the value with the predetermined value has a second result, wherein neither the first address nor the second addresses is contiguous to the predetermined address, execution of the predetermined processing instruction always implementing a change of control in program execution, wherein the value is one of a count value or a timer value, the value controlling when a thread switch between program threads is required.

20. (Currently Amended) ~~A~~ The data processing system of claim 18
~~wherein the processor further comprises~~ comprising:

DOCKET NO. SC11493TH

a memory for storing a plurality of program instructions;
an instruction register coupled to the memory via a data
bus for receiving the program instructions;
an instruction decoder coupled to the instruction register
for decoding the program instructions into specific
opcode values;
a control circuit coupled to the instruction decoder for
providing control signals in response to the specific
opcode values, the control circuit using a user
determinable control signal that selects instruction
group size;
address generation circuitry coupled to the control circuit
for receiving the control signals and creating the
jump address;
registers coupled to the address generation circuitry for
storing operands in response to the control circuit;
and
an arithmetic logic unit coupled to the address generation
circuitry and the control circuit, the arithmetic logic
unit processing the operands stored by the registers;
a storage device for storing a plurality of processing
instructions to be executed by the arithmetic logic
unit, the plurality of processing instructions arranged
in groups wherein each group is correlated to a
predetermined one of the plurality of program
instructions; and

DOCKET NO. SC11493TH

the arithmetic logic unit executing a predetermined processing instruction at a predetermined address and selecting a jump address based upon a value by providing a first address for the jump address if a comparison of the value with a predetermined value has a first result, and by providing a second address for the jump address if the comparison of the value with the predetermined value has a second result, wherein neither the first address nor the second address is contiguous to the predetermined address, execution of the predetermined processing instruction always implementing a change of control in program execution.

21. (Currently Amended) The data processing system of claim 20 wherein the control circuit further comprises a user determinable control signal that selects either a first structure of predetermined group sizes or a second structure of predetermined group sizes.

22.(Original) The data processing system of claim 20 wherein the address generation circuitry further comprises:
a multiplexer and combiner circuit coupled to the control circuit, the multiplexer and combiner circuit receiving at least one input signal that modifies the jump address.

DOCKET NO. SC11493TH

23. (Original) A software processing instruction stored on a storage medium which, when executed by a data processor results in creation of a jump address, the jump address being based upon a value and is provided as one of either a first address or a second address, the first address being selected if a comparison of the value with a predetermined value has a first result, the second address being selected if the comparison of the value with the predetermined value has a second result, neither of the second and third addresses being contiguous to an address assignment of the software processing instruction, the software processing instruction always causing a change of control in program execution by redirecting program execution in the data processing system to the jump address.